

2 Stroke Airless Striper Road Marking Machine 60 Pounds

Our Product Introduction

for more products please visit us on wagetrffic.com

Basic Information

- Place of Origin: China
- Brand Name: WAGE
- Model Number: HG-6L
- Minimum Order Quantity: 1 set
- Price: 2700-2900usd per set
- Packaging Details: Box
- Delivery Time: 1-3 weeks
- Payment Terms: L/C, T/T, Western Union, MoneyGram
- Supply Ability: 10 set per week



Product Specification

- Availability: In Stock
- Dimensions: 20 X 20 X 40 Inches
- Engine: 2-Stroke
- Hose Length: 50 Feet
- Max Flow Rate: 0.5 GPM
- Max Pressure: 3000 PSI
- Name: Airless Line Striper
- Noise Level: 68 DB
- Paint Capacity: 1 Gallon
- Power: Electric
- Type: Airless Line Striper
- Vibration Level: 2.5 M/s2
- Warranty: 1 Year
- Weight: 60 Pounds
- Highlight: **airless striper 60 Pounds.**

Product Description

Airless cold paint spraying line striper road marking machine single gun

Airless spraying line striper road marking machine single gun



Working Principle

Using gasoline engine to drive hydraulic plunger pump to form high pressure paint in the pump. The pressurized paint is transported to the airless gun through high pressure hose. Finally, the hydraulic pressure is released at the airless nozzle. After instantaneous atomization, the paint is sprayed to the ground to form a marking film layer. Normal temperature marking machine is usually suitable for the construction of underground parking spaces, plot plant area marking, a small number of pavement roads and other kinds of temperature marking.

WAGE HG-6L



- | | | | |
|---------------------|-----------------------|-------------------------------|-----------------------------------|
| 1. Handle | 8. Backflow valve | 14. Pressure regulating valve | 20. Solenoid valve |
| 2. Spray gun switch | 9. Tubeless tire | 15. Striping Pointer | 21. Gasoline engine pull starter |
| 3. steering switch | 10. Spray gun bracket | 16. Cross regulator | 22. Throttle, Damper, Oil circuit |
| 4. Pressure gauge | 11. Spray gun | 17. Micro switch | 23. Positioning wheel |
| 5. Paint pipes | 12. Nozzle | 18. Hydraulic plunger pump | 24. Front spraying gun holder |
| 6. Sucker | 13. Overflow valve | 19. Elbow, Marble | 25. Back spraying gun holder |
| 7. Paint bucket | | | |

1. Honda engine is used to ensure strong horsepower.
2. The front wheel positioning system and the vacuum pneumatic tire used in the rear wheel have good shock absorption effect, which can greatly reduce the line deformation caused by road surface fluctuation, and ensure that the marking edges and angles are neat.
3. The spray gun bracket can be adjusted in all directions to ensure the accuracy and convenience of line width.



5.5 HP gasoline engine



Spraying Gun

Parameter:

	HG-6L	HG-12L
power	5.5HP gasoline	6.5HP gasoline
Core pump	WAGE hydraulic piston pump	Precision Hydraulic Piston Pump
Marking mode	High pressure airless spraying	High pressure airless spraying
Working pressure	8-14Mpa	21Mpa MAX
Flow max	6L/min	12L/min
Spraying width	100-300mm(single gun)	50-500mm(DOUBLE GUNS)
Spraying thickness	0.2-0.4mm	0.2-0.4mm
Size (L*W*H)	1750*680*950mm	1700*750*1100mm
Weight	128kg	110kg

Working:



Application:



Contact:

Rita QU

[Xi'an Wage Traffic Infrastructure Installation Co.,LTD](#)

Mail: wagetrffic@hotmail.com Cell/ Whatsapp: +86 15591818803

Add:Room 401, Unit 2, Bilding 2, Shenglong Plaza, Weiyang Road, Xi'an, 710016, Shaanxi, China



Xian WAGE Traffic Infrastructure Installation Co., Ltd.



+86 15591818803



rita@wagetrffic.com



wagetrffic.com

Room 401, Unit 2, Biulding 2, Shenglong Plaza, Weiyang Road, Xi'an, 710016, Shaanxi, China