



Pavement Thermoplastic Striping Machine Bulge Thickness 3-5mm Adjusted

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: WAGE
- Certification: EMS OHSMS
- Model Number: HG-VM
- Minimum Order Quantity: 1 set
- Price: 6200 to 9250usd
- Packaging Details: box
- Delivery Time: 1 to 3 weeks
- Payment Terms: T/T, Western Union, MoneyGram, L/C
- Supply Ability: 10 set per week



Product Specification

- Paint Type: Thermoplastic
- Marking Type: Noice Marking
- Paint Tank: 120L
- Dispenser: 12kg
- Bulge Thichness: 3-5mm Adjusted
- Line Width: 15 20 30 45cm
- Application: Highway, Airport, Parking Lot
- Color: White, Yellow
- Dimensions: 1400*800*1000mm
- Marking Accuracy: ± 0.5 mm
- Marking Speed: 2-3m/min
- Marking Thickness: 1-2mm
- Marking Width: 50-150mm
- Material: Thermoplastic Paint
- Max. Marking Depth: 2mm



More Images



for more products please visit us on wagetraffic.com

Product Description

Thermoplastic Vibration line Road Line Marking Machine for noise marking

Vibration marking is a kind of marking which is widely used in developed countries. Its shape is concave and convex. When a car passes by, it will have a "boom" sound. It has a good warning and reminding effect on the driver, so it is also called noise markin



WAGE Vibration road line marking machine has the following functional:

1. Adopt automatic oil pressure stepless speed change driving mode, automatic walking, to ensure uniform and efficient construction effect;
2. The scribe adopts stainless steel insulating material coatings barrel and inserting manual mixing device to ensure the best temperature and shape of the melt.
3. Unique marking hopper, which makes the shape, spacing and height of marking protrusion precise and accurate, makes the marking of hot melt oscillation complete at one time, and has strong wear resistance and impact resistance.
4. Synchronized clutch glass bead sprayer makes the glass beads more evenly scattered on the marking line.
5. It is equipped with speed regulating gear shifting device and rear wheel positioning system to ensure that the equipment is fixed and straight ahead.



Parameters:

	HG-VM
motor	5.5HP Gasoline
moving speed	12km/h
Grade ability	15°MAX 15°
cylinder capacity	120kg/桶

Glass Micro sphere cylinder capacity	12kg/箱
Bulge thickness	3-5mm(adjustment)
standard width	150mm
size options	150/200/300/450mm(marking scoops replacement)
size (L*W*H)mm	1400*1100*1200mm
Weight	210kg

Main parts:



Dispenser



Liner controller



Shoe



Honda Gasoline

Construction spot:



We cherish and maintain the enterprise management principle of high standard and sophistication and the quality concept of quality enhancement for value increment. With the guidance of the users' product quality and economic benefits as the quality policy, we strive for the quality objective of zero defect rate. We believe the market-oriented enterprise operation; we prioritize quality for company development; we place corporation prestige in the fundamental position. United as a whole, all our staff are ready for forging ahead and expanding business. Consistently abiding by the principle of "customer first, quality first and reputation first", we endeavor to wholeheartedly serve customers at home and abroad with superior products and services.



Xian WAGE Traffic Infrastructure Installation Co., Ltd.

+86 15591818803

rita@wagetrain.com

wagetrain.com

Room 401, Unit 2, Building 2, Shenglong Plaza, Weiyang Road, Xi'an, 710016, Shaanxi, China