


## 2K Double Components Road Line Striping Marking Machine

Our Product Introduction

for more products please visit us on [wagetrffic.com](http://wagetrffic.com)

### Basic Information

- Place of Origin: China
- Brand Name: WAGE
- Certification: EMS OHSMS
- Model Number: HG 15GT
- Minimum Order Quantity: 1 set
- Price: 2400-2600usd per set
- Packaging Details: box
- Delivery Time: 1 to 3 weeks
- Payment Terms: L/C, T/T, Western Union, MoneyGram
- Supply Ability: 10 sets per week



### Product Specification

- Marking Model: Two Components
- Dispenser: Self Dropping
- Paint Cylinder Volume: 60L
- Glass Cylinder: 25kg
- Air Pressure: 0.4-0.6MPa
- Capacity: 100L/min
- Dimensions: 1400\*800\*1100mm
- Material: Stainless Steel
- Product Name: Two Component Road Marking Machine
- Spray Speed: 3-7m/min
- Spray Thickness: 1-4mm
- Spray Width: 50-400mm
- Weight: 200kg
- Highlight: **2K Road Line Striping Marking Machine, Double Components Road Line Marking Machine**



### More Images



## Product Description

### Scraping two compoent road line marking machine

2024 New version



OLD version



### **General information:**

two-component marking series is divided into spraying and scraping two construction processes, two coatings with the aid of two pumps or two paint barrels after mixing chemical reaction to form marking. Compared with the hot melt marking, the two-component marking construction has the advantages of environmental protection, high wear resistance, good reflectivity, long service life and easy construction.



HG-20MM-II is to put two kinds of coatings in the same barrel separated. After discharging the coatings from the tank, the coatings are fully stirred by an electric stirring shaft. After mixing in the crossing hopper, the chemical reaction is carried out. Finally, the marking is done through the crossing hopper. Compared with spraying two-component marking, scraping marking has the advantages of thicker marking thickness, longer wear resistance, better reflectivity and more uniform mixing.

**Parameter:**

	HG-15GT
Marking mode	<b>Double compartment scraping</b>
Agitation speed	650r/min
Glass Micro sphere cylinder capacity	25kg
Spraying system	Self dropping
Paint cylinder capacity	60L/ tank x 2↑cylinder
Marking thickness	1.2-2.5mm adjustment within ranges
Standard thickness	150mm
Width optional	100/200/300/400/450mm(scoops replacement)
Size (L*W*h)	1200*900*1100mm
Weight	162kg

**Construction:**





**Contact:**

Rita QU

[Xi'an Wage Traffic Infrastructure Installation Co.,LTD](#)

Mail: [wagetrffic@hotmail.com](mailto:wagetrffic@hotmail.com) Cell/ Whatsapp: +86 15591818803

Add:Room 401, Unit 2, Bilding 2, Shenglong Plaza, Weiyang Road, Xi'an, 710016, Shaanxi, China



**Xian WAGE Traffic Infrastructure Installation Co., Ltd.**



+86 15591818803



[rita@wagetrffic.com](mailto:rita@wagetrffic.com)



[wagetrffic.com](http://wagetrffic.com)

Room 401, Unit 2, Biulding 2, Shenglong Plaza, Weiyang Road, Xi'an, 710016, Shaanxi, China